

Zabbix agent

```
# pkg search zabbix | grep agent
```

```
zabbix4-agent-4.0.45      Enterprise-class open source distributed monitoring (agent) LTS
zabbix5-agent-5.0.33      Enterprise-class open source distributed monitoring (agent) LTS
zabbix6-agent-6.0.16      Enterprise-class open source distributed monitoring (agent)
zabbix62-agent-6.2.9      Enterprise-class open source distributed monitoring (agent)
zabbix64-agent-6.4.1      Enterprise-class open source distributed monitoring (agent)
```

Встановлення zabbix6-agent-6:

```
pkg install zabbix6-agent-6
```

Копіюємо каталог конфігурацій:

```
cp -a /usr/local/etc/zabbix6/ /usr/local/etc/zabbix6.orig
```

Перейдемо до каталогу

```
cd /usr/local/etc/zabbix6/
```

у конфізі додамо параметри:

```
tee -a ./zabbix_agentd.conf << EOF
```

```
Include=/usr/local/etc/zabbix6/zabbix_agentd.conf.d/*.conf
Include=/usr/local/etc/zabbix6/zabbix_agentd.conf.d/*.local
EOF
```

```
tee ./zabbix_agentd.conf.d/agent.local << EOF
```

```
Server=172.16.0.21
ServerActive=172.16.0.21
```

```
Hostname=example.com  
EOF
```

nano ./zabbix_agentd.conf.d/agent.local Додамо в автозавантаження:

```
sysrc zabbix_agentd_enable=YES
```

```
service zabbix_agentd start
```

From:
<https://ndp.pp.ua/> - my NoDeny Wiki

Permanent link:
https://ndp.pp.ua/doku.php/freebsd/zabbix_agent?rev=1682414317

Last update: **25/04/2023 09:18**

