

Zabbix agent

```
# pkg search zabbix | grep agent
zabbix5-agent-5.0.45      Enterprise-class open source distributed monitoring (agent) LTS
zabbix6-agent-6.0.39      Enterprise-class open source distributed monitoring (agent)
zabbix7-agent-7.0.11      Enterprise-class open source distributed monitoring (agent)
zabbix72-agent-7.2.5      Enterprise-class open source distributed monitoring (agent)
```

Встановлення zabbix7-agent:

```
pkg install zabbix7-agent
```

Копіюємо каталог конфігурацій:

```
cp -a /usr/local/etc/zabbix7/ /usr/local/etc/zabbix7.orig
```

Перейдемо до каталогу

```
cd /usr/local/etc/zabbix/
```

у конфізі додамо параметри:

```
tee -a /usr/local/etc/zabbix/zabbix_agentd.conf << EOF

Include=/usr/local/etc/zabbix7/zabbix_agentd.conf.d/*.conf
Include=/usr/local/etc/zabbix7/zabbix_agentd.conf.d/*.local
EOF

tee /usr/local/etc/zabbix7/zabbix_agentd.conf.d/agent.local << EOF
Server=172.16.0.21
ServerActive=172.16.0.21
Hostname=example.com
```

EOF

```
nano /usr/local/etc/zabbix7/zabbix_agentd.conf.d/agent.local
```

Додамо в автозавантаження:

```
sysrc zabbix_agentd_enable=YES
```

```
service zabbix_agentd start
```

From:

<https://ndp.pp.ua/> - my NoDeny Wiki

Permanent link:

https://ndp.pp.ua/doku.php/freebsd/zabbix_agent?rev=1744105825

Last update: **2025/04/08 12:50**

