

Корисні функції Perl

I remember seeing this awhile ago on this list and saved it:

```
#bin2dec:
$out = unpack("N", pack("B32", substr("0" x 32, $in, -32)));
#bin2hex:
$out = unpack("H8", pack("B32", substr("0" x 32, $in, -32)));
#bin2oct:
$out = sprintf "%o", unpack("N", pack("B32", substr("0" x 32, $in, -32)));
#dec2bin:
$out = unpack("B*", pack("N", $in));
#dec2hex:
$out = unpack("H8", pack("N", $in));
#dec2oct:
$out = sprintf "%o", $in;
#hex2bin:
$out = unpack("B32", pack("N", hex $in));
#hex2dec:
$out = hex $in;
#hex2oct:
$out = sprintf "%o", hex $in;
#oct2bin:
$out = unpack("B32", pack("N", oct $in));
#oct2dec:
$out = oct $in;
#oct2hex:
$out = unpack("H8", pack("N", oct $in));
#hex2ansi
$out = pack('H*', $in);
#is ipv4
my $ok = '10.10.255.1' =~ '\b((25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]? )(\.|$)){4}\b'? 1: 0;
```

```
sub ip2bin {
    my $ip = shift;
    my $bin = join('.', map substr(unpack("B32",pack("N",$_)),-8), split(/\./,$ip));
    return $bin;
    return unpack('B32', pack('C4C4C4C4', split(/\./, $ip)));
}

sub bin2ip {
    my $bin = shift;
    return join '.', unpack('C4C4C4C4', pack('B32', $bin));
}

sub ip2num {
    my $ip = shift;
    return unpack("N",pack("C4",split(/\./,$ip)));
    return unpack('N',pack('C4',split(/\./,$_[0])));
}

sub num2ip {
    my $num = shift;
    my $res = (($num>>24) & 255) ".". (($num>>16) & 255) ".". (($num>>8) & 255) ".". ($num & 255);
    return $res;
}

# decode utf like \x{42f}
print Dumper(%mydata) =~ s/\\x\{([0-9a-f]{2,})\}/chr hex $1/ger;
#https://stackoverflow.com/a/50511147/14644785
```

From:
<https://ndp.pp.ua/> - my NoDeny Wiki

Permanent link:
<https://ndp.pp.ua/doku.php/perl/helpfull?rev=1658937875>

Last update: **27/07/2022 16:04**

